



HERKULES HM 1100 BY HEDSON

Fast mobile lifts for service jobs with interchangeable lifting devices











- PERFORMANCE ABOVE ALL ------



FLEXIBLE AND SPACE SAVING LIFTS

With the lifts horizontal moveable swivel arms it is easy to reach the vehicles' original lifting points

With a Herkules HM 1100 by Hedson lift there is no installation necessary in the work shop, the lift is ready to use immediate. And with an additional set of wheels it is mobile in the shop. The lift is equipped with swivel arms which easily reach the vehicles' original lifting points.

In the workshop it is important that the environment is clean and explosion proof. All Herkules by Hedson lifts uses pneumatic lifting technology, which means they are driven by compressed air, no electrical connection is required. In the workshops air supply is common and uses for a clean, dependable and almost maintenancefree operation.

Nearly 85 % of all car damages require the worker to work in a stooped position. This causes fatigue and can also lead to long-term health problems. With a lift the work can be done in an ergonomically correct upright position, which also increase the work efficiency and improve the quality by better visual control opportunities.

- Fast lifting
- No installation is required
- Silicone free (PWIS-free, stands for paint-wetting impairment substances)
- On-ground or flush mounted installations

						_
: • :	 		•:	: :	1.17	1.1

ON-GROUND

Simply fix with screws and dowels, and the lift is ready for immediate use.

Sense and the second second

FLUSH MOUNTED Flush mounted to concrete or grids.





© Hedson Technologies AB 2017 The manufacturer reserves the right to introduce technical modifications.


Sweden Phone + 46 40 53 42 00 **Germany** Phone +49 561-589070 North America Phone +1 905-339 28 00

France Phone +33 3-44 26 87 76 info@hedson.com www.hedson.com

Loading capacity	2,8 tons
Air supply	6 bar
Weight	510 kg
Working height - HM 1100-01 - HM 1100-04	~1100 mm ~1000 mm
Lifting height - HM 1100-01 - HM 1100-04	930 mm 825 mm
Object height - HM 1100-01	115 mm
Pit depth - HM 1100-04	115 mm

TECHNICAL DATA

Swivel arms fully adjustable



2 00 Germany Phone +4