



# BY HEDSON

### Cleaning process with re-circulating solvent and clean solvent, which saves time and solvent

The Drester boxer solvent cleaning process together with the unparalleled reliability and durability, makes the Drester by Hedson equipment a better choice and an investment that will increase the profitability. These gun cleaners are also equipped with hoods for protections from splashing and enable different types of ventilation: Drester Airvent, Drester Minivent or central ventilation. Drester Boxer for solvent-based cleaning offers two models; a compact-size unit and a full-size unit.



## **PATENTED MAGNETIC GUN HOLDER**

All Drester Boxer by Hedson gun cleaners also feature a patented magnetic gun holder which simplifies the cleaning and use of the gun cleaner. The magnetic gun holder pulls the trigger to open the paint channel and fixates a gun in seconds, in one simple step. It fixates the gun in a position where the gun's air channels are protected, facing downwards, so there is no risk of solvent entering the air channels.



#### **ERGONOMIC**

A small footprint - easy to operate and user friendly and ergonomic. The operator can easily see what footprint to use



## **SAFETY**

The gun cleaners is equipped with a hood for protections from splashing and enable different types of ventilation



#### **TECHNICAL SPECIFICATION**

Drester Boxer Double Solvent Part.no. DB22S (standard unit)

Shipment dimensions (DB22S) 1 pcs on pallet, 760\*900 mm, 88 kg

Drester Boxer Quattro Solvent Part.no. DB44S (standard unit)

Shipment dimensions (DB44S) 1 pcs on pallet, 1250\*760 mm, 100 kg

#### DRESTER BOXER DOUBLE SOLVENT

Weight 75 kg (165 lb)

Compressed air needed 7-12 bar (110-180 psi) 150 l/min (6 cfm)

Ventilation capacity 200-500 m<sup>3</sup>/h (118-294 cfm) -> 0,2-0,5 m/s (0,7-1,6 fps)

> Height 1510 mm (59,5")

Width 835 mm (33,0")

Max depth 650 mm (25,5")

Depth at the floor 610 mm (24,0")

Extractor diameter 125 mm (5")

## **DRESTER BOXER QUATTRO SOLVENT**

Weight 105 kg (230 lb)

7-12 bar (110-180 psi) 150 l/min (6 cfm) (450 l/min (16 cfm) Compressed air needed

with DRESTER AIRVENT 11660)

Ventilation capacity 240-600 m<sup>3</sup>/h (141-353 cfm) -> 0,2-0,5 m/s ( 0,7-1,6 fps)

> Height 1510 mm (59,5")

Width 1185 mm (46,7")

Max depth 650 mm (25,5")

Depth at the floor 610 mm (24,0")

Extractor diameter 125 mm (5")

