



DRESTER X-SERIES BY HEDSON

High-quality gun cleaners with excellent cleaning performance

The robust Drester X-series by Hedson are aimed towards workshops and industries with a heavy work load. The X-series features three models; one single with manual work station, one single with automatic work station and one double with two work stations, both manual and automatic.

- Welded stainless working platform
- Adjustable wash cycle, 1-4 min
- Spray Gun Storage, up to 7 gun storage
- Washes all types of guns – no limit to gravity fed guns
- Ergonomic with less depth



ROBUST & EASY CLEANING

Robust gun cleaner developed for workshops and industry with extra heavy workload. With its welded stainless working platform it is easy to keep clean



EFFICIENT WORKFLOW

The automatic units have adjustable wash cycle, 1-4 min, washes all types of guns and have no limit to gravity fed guns. Every unit has a spray gun storage, with possibility to store up to 7 spray guns



ERGONOMIC

With less deep space, every unit is easily maneuvered and more ergonomic for the operator when cleaning

TECHNICAL SPECIFICATION

Drester X-series Manual	Part.no. DIX11M
Drester X-series Automatic	Part.no. DIX11
Shipment dimensions (DIX11)	1 pcs on pallet, 760*900 mm, 83 kg
Drester X-series Double	Part.no. DIX22
Shipment dimensions (DIX22)	1 pcs on pallet, 760*900 mm, 106 kg

DRESTER X-SERIES MANUAL & AUTOMATIC

Weight	75 kg (165 lb)
Height	1510 mm (59,5")
Width	835 mm (33")
Max depth	650 mm (25,5")
Depth at the floor	610 mm (24")
Compressed air needed	7-12 bar (110-180 psi) 90 l/min (3 cfm) 1 pump 370 l/min (14 cfm) incl. AIRVENT 11660 in operation
Ventilation capacity	200-500 m3/h (118-294 cfm) -> 0,2-0,5 m/s (0,7-1,6 fps)
Pump capacity	10 l/min
Maximum drum size	60 litres
Solvent pressure	2 bar (30 psi)
Extractor diameter	125 mm (5")

DRESTER X-SERIES DOUBLE

Weight	95 kg (140 lb)
Height	1510 mm (59,5")
Width	1185 mm (46,7")
Max depth	650 mm (25,5")
Depth at the floor	610 mm (24")
Compressed air needed	7-12 bar (110-180 psi) 180 l/min (6 cfm) 2 pumps 460 l/min (17 cfm) incl. AIRVENT 11660 in operation
Ventilation capacity	240-600 m3/h (141-353 cfm) -> 0,2-0,5 m/s (0,7-1,6 fps)
Pump capacity	10 l/min
Maximum drum size	60 liters
Solvent pressure	2 bar (30 psi)
Extractor diameter	125 mm (5")

OPTIONS

Minivent (3ph. 380V, 250W) (Double)	Part.no. 2050
Minivent (3ph. 415V, 250W) (Double)	Part.no. 2055
Airvent (Ø125 mm)	Part.no. 11660
Magnetic gun holder	Part.no. 15650
2-gun spray cradle	Part.no. 9290
Collecting tray	Part.no. 10960
Moisture trap	Part.no. 4020
Extension tube	Part.no. 10455

Kit for suction-fed gun	Part.no. 15640
Adapter for side-fed gun	Part.no. 17270
Adaption Kit DIX22-RDX needed for Dynamic Triple system with DIX22, Drester X-series Double	Part.no. 230891